MAPEFLOOR CPU+/TC
Declaration of Performance
N. CPR-IT1/0916

DECLARATION OF PERFORMANCE N. CPR-IT1/0916

1) Unique identification code of the product-type: **MAPEFLOOR CPU+/TC**

2) Intended uses: **Three-component cementitious screed material modified by polymer for internal use in floor construction**

3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**

4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)

5) Harmonized standards: **EN 13813:2002**

Notified bodies: **CSI SPA, N. 0497**

6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	**Class B_{FL}-s1**
Release of corrosive substances:	**CT**
Water permeability:	**NPD**
Water vapour permeability:	**NPD**
Compressive strength:	**C40**
Flexural strength:	**F7**
Wear resistance:	**AR0,5**
Sound insulation:	**NPD**
Sound absorption:	**NPD**
Thermal resistance:	**NPD**
Chemical resistance:	**NPD**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Lorenzo Martino – *Corporate Quality Management***

Milan, 16/12/2022 ……

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	*Reaction to fire updated*

MAPEFLOOR CPU+/TC
CE MARKING
Annex to DoP N. CPR-IT1/0916

ADESIVI · SIGILLANTI · PRODOTTI CHIMICI PER L'EDILIZIA

CE 0497	MAPEI **Via Cafiero, 22 – 20158 Milano (Italy)** **www.mapei.it**
21 **CPR-IT1/0916** **EN 13813** **MAPEFLOOR CPU+/TC** *Three-component cementitious screed material modified by polymer for internal use in floor construction*	
Reaction to fire:	Class B_{FL}-s1
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C40
Flexural strength:	F7
Wear resistance:	AR0,5
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking,*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*